



KENZO AUTOMOTIVE BATTERY



SAKTHI ACCUMULATORS PVT LTD
(An ISO 9001:2015 & ISO 14001:2015 Certified Company)



KENZO AUTOMOTIVE BATTERY



TECHNICAL SPECIFICATIONS OF KENZO MOTORCYCLE BATTERY

Kenzo Two Wheeler Model No.	Capacity (Ah)	Voltage (V)	Charged Weight (in Kg) (+/-0.05 kg)	Dimensions in mm (L*W*H) (+/- 2mm)
KZ 2.5 LC	2.5	12	1.10	80 x 70 x 105
KZ Z4	3	12	1.40	113 x 70 x 85
KZ Z5	4	12	1.89	113 x 70 x 105
KZ 5 LB	5	12	1.92	120 x 60 x 130
KZ 7 LB	7	12	2.43	150 x 60 x 130
KZ 9 LB	9	12	3.05	135 x 75 x 139

TECHNICAL SPECIFICATIONS OF KENZO AUTOMOTIVE BATTERY

Battery Type		Specification				Dimensions in mm		
KENZO Part Number	OLD JIS Designation	Capacity @ C20	Capacity @ C5	Nominal Cold Cranking Ampere Amps	Nominal Reserve Capacity	Length +/- 5mm	Width +/- 5mm	Height +/- 5mm
		Ah	Ah	CCA A@ -18°C	RC in mins	mm	mm	mm

KENZO CAR SERIES (JIS)

34B19 R/L	NS40	32	26	240	38	187	129	227
38B20 R/L	NS40	35	28	265	43	197	129	227
55B24 R/L	NS60PMF/LPMF	45	36	380	75	238	129	227

KENZO (DIN) SERIES

DIN44	545106036	44	35	450	86	210	170	190
DIN55	555155050	55	44	500	103	240	170	190
DIN66	566112061	66	53	610	121	295	170	190
DIN74	574102069	74	59	690	131	295	170	190
DIN90	590109080	90	72	800	162	352	175	190
DIN100	600109090	100	80	900	181	352	175	190

KENZO COMMERCIAL SERIES

55D23 R/L	D23	60	48	320	74	232	173	225
80D26 R/L	N50ZPM/ZLPMF	70	56	500	110	260	173	225
95D31 R/L	N70PMF/LPMF	80	64	600	125	306	173	225
105D31 R/L	NX120-7MF/LPMF	90	72	670	160	306	173	225
N100	105E41L	100	80	650	190	410	170	240
N120	115F51	120	96	750	240	510	210	255
N150	145G51	150	120	900	300	510	210	255
N200	190H52	200	160	1100	400	515	270	255

ALSO AVAILABLE

A comprehensive range of Sakthi Sunlite - C 10 Solar Batteries, Legend - C 20 UPS Batteries and 2V Stationary Cells

AUTHORISED DEALER

Statutory Notice: All batteries contain lead, which is harmful to humans and the environment. As per statutory requirements, the used battery must be returned to the authorized dealer, manufacturer or at the designated collection centers.